

Supply Voltage	: 24 V dc \pm 10% - common
Maximum Ripple Voltage	: 0.1 V pp
Current Consumption (no signal)	: 60 mA
Current Consumption (max. load)	: 120 mA
Temperature Range	: -20 to +60°C (-4 to +140°F)
High Frequency Cut (-2,5dB)	: 1-1.4-2-2.8-4-5.6-8-11.2-16 kHz
Slope	: 18dB/octave see curve
Low Frequency cut (-2,5dB)	: 40-60-80-113-160-226-320-452-640 Hz
Slope	: 18dB/octave see curve
Input Overload Level	: +21dBu (note 1)
Input Impedance (20 Hz - 20 kHz)	: 22 Kohms \pm 15% Balanced Floating
Output Overload Level	: +21 dBu (RL=600ohms)(note 1)
Output Impedance	: 40 ohms Balanced Floating
Minimum Load Impedance	: 200 ohms
Gain	: 0 dB \pm 0.5 dB
Distortion 40 Hz to 200 Hz	: less than 0.5%
Distortion 200 Hz to 20 kHz	: less than 0.2%
Noise referred to Input	: -103 dBu A-curve
Connector	: Tuchel T 2700
Standard Colour	: Dull Black
Mechanical Outline	: Front 40 x 190 mm Depth 103 mm (1.58x7.5") (4.05")

Note 1: The overload indicator is activated at input levels above approx. +20dBu.

